KB1212 12V 1.2Ah

The KB Standard series consists in VRLA batteries with AGM technology (Absorbent Glass Material), with a design life of 3-5 years and are designed for general applications such as UPS, telecommunications and electrical applications.

Performance Characteristics

Nominal Voltage	12V	
Dimensions	Length (mm / inch)	97 / 3.82
	Width (mm / inch)	43 / 1.69
	Height (mm / inch)	52 / 2.05
	Total Height (mm / inch)	58 / 2.28
Approx Weight	(Kg / lbs)	0.51 / 1.12
Design Life	5 years	
Terminal	F1	
Container Material	ABS	
Rated Capacity	1.20Ah / 0.060A	(20hr, 1.75V / cell, 25ºC / 77ºF)
	1.13Ah / 0.113A	(10hr, 1.75V / cell, 25ºC / 77ºF)
	1.05Ah / 0.209A	(5hr, 1.75V / cell, 25ºC / 77ºF)
	0.792Ah / 0.792A	(1hr, 1.60V / cell, 25ºC / 77ºF)
Max. Discharge Current	18A (5s)	
Internal Resistance	95.0 mΩ	
Operating Temp. Range	Discharge : -20 ~ 50ºC (-4 ~122ºF) Charge : -20 ~ 50ºC (-4 ~ 122ºF) Storage : -20 ~ 50ºC (-4 ~ 122ºF)	
Cycle Use	Initial Charging Current less than 0.30A Voltage: 14.4V ~ 15.0V at 25ºC (77ºF) Temp. Coefficient: -30mV/ºC	
Standby Use	Initial Charging Current less than 0.30A Voltage: 13.5V ~ 13.8V at 25ºC (77ºF) Temp. Coefficient: -18mV/ºC	
Capacity affected by Temperature	40ºC (104ºF)	103%
	25ºC (77ºF)	100%
	0ºC (32ºF)	86%
Self Discharge	Fully charged Kaise Standard Series batteries may be stored for up to 6 months at 25ºC (77ºF) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Dimensions and Terminal (Unit: mm (inches))



Applications

Alarm systems
Cable television
Communications Equipment
Control Equipment
Computers
Electronic Cash Registers
Electric Test Equipment
Emergency lighting systems
Fire & Security
Geophysical equipment
Marine equipment
Medical equipment
Micro processor based office machines
Portable cine & Video lights
Solar powered systems
Telecommunications systems
Television & Video recorders
Toys
Uninterruptible power supply systems
Vending machines

Certifications

ISO 9001 / ISO 14001

Discharge Current vs. Discharge Voltage

Final discharge voltage V/CELL	1,8	1,75	1,7	1,6
Discharge current (A)	I ≤ 0,1CA	0.25CA ≥ I > 0.1CA	0.55CA ≥ I > 0.25CA	I > 0.55CA

Discharge Constant Current (Amperes) at 77ºF (25ºC)

Volts/ cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.80V	3.30	2.51	1.72	1.32	0.671	0.294	0.200	0.110	0.058
1.75V	3.59	2.66	1.85	1.36	0.695	0.311	0.209	0.113	0.060
1.70V	3.86	2.80	1.98	1.40	0.720	0.316	0.218	0.115	0.061
1.65V	4.72	2.98	2.12	1.44	0.744	0.322	0.221	0.118	0.062
1.60V	4.75	3.11	2.32	1.52	0.792	0.331	0.226	0.119	0.064

Discharge Constant Power (Watts per cell) at 77ºF (25ºC)

Volts/ cell	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.80V	6.12	4.82	3.50	2.49	1.27	0.574	0.388	0.214	0.118
1.75V	6.82	4.98	3.66	2.51	1.29	0.590	0.398	0.219	0.119
1.70V	7.52	5.14	3.80	2.54	1.32	0.598	0.406	0.224	0.122
1.65V	8.22	5.30	3.98	2.55	1.37	0.608	0.418	0.226	0.123
1.60V	8.92	5.60	4.24	2.56	1.45	0.626	0.426	0.230	0.126

(Note) The above characteristics data are average values obtained within three charge/discharge cycles not the mimimum values.

KB1212 12V 1.2Ah

Charging Characteristics



Discharge Characteristic



The effect of temperature on capacity



The effect of discharge depth on cycle life



Curves of self-discharge



The effect of temperature on float life



IMPORTANT NOTE: The specifications presented herein are subject to revision without notice.

2024/V/K

Contacto
customer.energy@tempelgroup.com
www.tempelgroup.com

Tempel Group en el mundo
HOUSTON · BARCELONA · MADRID · VALENCIA · BILBAO · SEVILLA · LISBOA · PORTO · ROMA · BUENOS AIRES · LIMA
SANTIAGO DE CHILE · BOGOTÁ · SÃO PAULO · CIUDAD DE MÉXICO · MONTERREY · CIUDAD DE PANAMÁ · MONTEVIDEO · QUITO