KB21500 2V 1500Ah

The Kaise Ultra Long Life series of VRLA batteries is known for having the most reliable and highest quality of the entire industry. Built with AGM technology, these batteries reach a service life of 20 years.

Performance Characteristics

Nominal Voltage	2V	
Dimensions	Length (mm / inch)	355 / 14.0
	Width (mm / inch)	337 / 13.3
	Height (mm / inch)	330 / 13.0
	Total Height (mm / inch)	342 / 13.5
Approx. Weight	(Kg / lbs)	80.0 / 176.3
Design Life	20 years	
Terminal	M8	
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.	
Rated Capacity	1500.0Ah / 150.0 A	(10hr, 1.80V/cell, 25ºC / 77ºF)
	1308.5Ah / 261.7 A	(5hr, 1.75V/cell, 25ºC / 77ºF)
	1161.0Ah / 387.0 A	(3hr, 1.75V/cell, 25ºC / 77ºF)
	885.1Ah / 885.1A	(1hr, 1.65V/cell, 25ºC / 77ºF)
Max. Discharge Current	6000A (5s)	
Internal Resistance	≤040mΩ	
Operating Temp. Range	Discharge : -20 ~ 60ºC Charge : -0 ~ 50ºC Storage : -20 ~ 60ºC	
Cycle Use	Initial Charging Current less than 300A Voltage: 2.43V ~ 2.47V at 25ºC (77ºF) Temp. Coefficient: -4mV/ºC/Cell	
Standby Use	Initial Charging Current less than 300A Voltage: 2.27V~ 2.30V at 25ºC (77ºF) Temp. Coefficient: -3mV/ºC/Cell	
Capacity affected by Temperature	40ºC (104ºF)	103%
	25ºC (77ºF)	100%
	0ºC (32ºF)	86%
Self Discharge	Fully charged Kaise Solar Series batteries may be stored for up to 6 months at 25ºC (77ºF) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Dimensions and Terminal (Unit: mm (inches))



Applications

Renewable Energy
Alarm systems
Electric Test Equipment
Emergency lighting systems
Marine equipment
Telecommunications systems

Certifications

ISO 9001 / ISO 14001

Discharge Current vs. Discharge Voltage

Final discharge voltage V/CELL	1.8	1.75	1.7	1.6
Discharge current (A)	I ≤ 0.1CA	0.25CA ≥ I > 0.1CA	0.55CA ≥ I > 0.25CA	I > 0.55CA

Constant Current Discharge (Amperes) at 25ºC (77ºF)

Volts/cell	30min	1h	2h	3h	5h	8h	10h
1.80V	1216	793.4	491.7	375.0	255.0	179.5	150.0
1.75V	1272	825.0	509.9	387.0	261.7	182.6	151.9
1.70V	1331	856.3	528.4	398.9	268.5	185.1	154.0
1.65V	1393	885.1	546.4	410.0	275.6	188.1	156.3
1.60V	1451	916.5	564.4	423.1	283.0	190.2	158.2

Constant Power Discharge (Watts per cell) at 25ºC (77ºF)

Volts/cell	30min	1h	2h	3h	5h	8h	10h
1.80V	2301	1527	950.7	728.4	498.5	353.5	296.4
1.75V	2383	1578	981.0	748.7	509.9	358.8	299.8
1.70V	2468	1628	1012	768.4	521.3	363.2	303.5
1.65V	2556	1673	1041	786.4	533.3	368.0	307.7
1.60V	2635	1722	1070	808.1	545.5	371.4	311.1

(Note) The above characteristics data are average values obtained within three charge/discharge cycles not the mimimum values.

KB21500 2V 1500Ah

Charging Characteristic



Discharge Characteristics



Cycle Life In Relation To Depth Of Discharge



Relationship Between Charging Voltage And Temperature



Temperature Effects On Capacity



Storage Characteristics



Effect Of Temperature On Long Term Life



Charge Characteristic Curve For Standby Use



IMPORTANT NOTE: The specifications presented herein are subject to revision without notice.

2024V1/R

Contacto
customer.energy@tempelgroup.com
www.tempelgroup.com

Tempel Group en el mundo
HOUSTON · BARCELONA · MADRID · VALENCIA · BILBAO · SEVILLA · LISBOA · PORTO · ROMA · BUENOS AIRES · LIMA
SANTIAGO DE CHILE · BOGOTÁ · SÃO PAULO · CIUDAD DE MÉXICO · MONTERREY · CIUDAD DE PANAMÁ · MONTEVIDEO · QUITO