UPS SERIES | ONLINE RACK TOWER

The ONLINE RACK TOWER UPS 1-3kVA is a new-generation, low-power UPS from KAISE. Both input and output are single-phase, with an output factor of 1.0. With 94% efficiency, it can achieve energy savings and reduce customer costs as a result.

Colourful LCD

Multifunctional Bracket

Optimized Battery Configuration 9Ah

The LCD Panel Can be Rotated

Features

- Rack/Tower convertible design
- Online double conversion with full digital control
- Wide input voltage range: 110~300Vac
- Input power factor 0.99 with PFC
- Selectable output voltage: 208/220/230/240Vac
- Smart charger design for optimized battery performance
- Maximum charging current can be expanded to 12A (Long run unit)
- ECO mode operation for energy saving
- Generator compatible
- Hot-Swappable battery design
- Cold start
- Intelligent fan speed regulation
- Versatile LCD human-computer interface
- Multiple communication interface: RS232 (SNMP card optional)
- Multiple protection function: short-circuit,overload,overheat, battery overcharge and overdischarge, output low voltage and fan fault alarm

UPS SERIES | ONLINE RACK TOWER

Kaise®

Technical Specifications

MODEL	KURTON1000-IB	KURTON2000-IB	KURTON3000-IB
Capacity (VA/W)	1000/1000	2000/2000	3000/3000
INPUT			
Nominal Voltage (Vac)	208/220/230/240		
Operating Voltage Range (Vac)	110~300 (176~264 @ 100% load)		
Power Factor	≥1.0		
Bypass Frequency Range (Hz)	40~70 (50/60 Auto-Sensing)		
OUTPUT			
Nominal Voltage (Vac)	208/220/230/240		
Voltage Regulation	±1%		
Power Factor	1.0		
Output Frequency (Hz)	Line mode: 46~54 or 56~64; Bat. mode: (50/60±0.1%)		
Crest Factor	3:1		
Harmonic Distortion (THDv)	≤3% Linear load; ≤5% Non linear load		
Transfer Time (ms)	AC mode to Bat.mode: 0; Inverter to Bypass: 4 (Typical)		
Waveform	Pure Sinewave		
Number of Schuko	2		
EFFICIENCY			
AC Mode	Up to 89%	Up to 90%	Up to 91%
ECO Mode	Up to 95%	Up to 96%	Up to 97%
BATTERY			
Battery Type	VRLA (Lead acid maintenance free battery)		
Battery Voltage (Vdc)	24 / 36	48 / 72	72
Battery Capacity (Ah)	S: 7/9; H: Depends on the capacity of external batteries		
Charging Current (Max.) (A)	1	1	1
MANAGEMENT			
LED Display	Line mode, Bat.mode, ECO mode, Bypass mode, Battery low voltage, Overload & UPS fault		
LCD Display	Input voltage, Input frequency, Output voltage, Output frequency, Load percentage, Battery voltage, Inner temperature& Remaining battery backup time		
ENVIRONMENTAL			
Operating Temperature (℃)	0~40		
Storage Temperature (℃)	-25~55		
Humidity Range	20~95%RH @ 0~40℃ (Non condensing)		
Altitude (m)	< 1500 m		
Noise Level (dB)	<55 - 1m		
PHYSICAL			
Dimensions WxDxH (mm)	440*460*86.5 (2U)	440*600*86.5 (2U)	440*600*86.5 (2U)
Weight (kg)	14	25	26
STANDARDS			
Safety	IEC/EN 62040-1, IEC/EN 62477-1		
EMC	IEC/EN62040-2, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8		

1. Specifications are subject to change without prior notice
2. Data above are typical values for reference only, not as a basis for engineering design

2026/V1/K

Contacto
customer.energy@tempelgroup.com
www.tempelgroup.com

Tempel Group en el mundo
HOUSTON · BARCELONA · MADRID · VALENCIA · BILBAO · SEVILLA · LISBOA · PORTO · ROMA · BUENOS AIRES · LIMA
SANTIAGO DE CHILE · BOGOTÁ · SÃO PAULO · CIUDAD DE MÉXICO · MONTERREY · CIUDAD DE PANAMÁ · MONTEVIDEO · QUITO

tempel group